## INTRODUCING... PINK® PARTITION (24)

## PARTITION

## Fletcher<sup>®</sup> Insulation

For further information:



info@insulation.com.au

www.insulation.com.au

As the world becomes a noisier place the importance of excellent acoustic design becomes imperative. Acoustic performance is desirable in a number of industries such as corporate, healthcare and education where sound reduction between rooms is required. Pink<sup>®</sup> Partition insulation is specifically designed to act as a sound barrier to reduce the level of noise transmitted from one room to another. Reducing sound transmission contributes to the overall ambience of a building and creates a more comfortable internal environment.

When installed in external wall applications, Pink<sup>®</sup> Partition insulation reduces the flow of external noise transmitted into the building. It also provides excellent thermal properties thereby improving the buildings thermal comfort and energy efficiency.

Pink<sup>®</sup> Partition insulation has never been easier to install. The range features a softer feel for comfortable handling and includes a variety of dimensions specially designed to friction fit into steel stud frames. This reduces the amount of cutting required and allows for quicker installation.



| Pink <sup>®</sup> Partition 24 insulation technical specifications |                         |                 |                 |             |              |
|--|-------------------------|-----------------|-----------------|-------------|--------------|
| Material R-value   | Nominal Thickness<br>mm | Size<br>mm x mm | Pieces per Pack | m² per Pack | Product Code |
| R1.1   | 38                      | 2700 x 600      | 12              | 19.40       | 901023       |
| R1.4   | 50                      | 1200 x 450      | 12              | 6.50        | 903551       |
|  |                         | 1200 x 600      | 12              | 8.60        | 903552       |
|  |                         | 2700 x 600      | 12              | 19.40       | 901024       |
| R1.8   | 64                      | 2700 x 600      | 10              | 16.20       | 901025       |
| R2.1   | 75                      | 1200 x 450      | 10              | 5.40        | 903553       |
|  |                         | 1200 x 600      | 10              | 7.20        | 903554       |
| R2.5   | 90                      | 1200 x 450      | 8               | 4.30        | 903555       |
|  |                         | 1200 x 600      | 8               | 5.80        | 903556       |
| R2.8   | 100                     | 1200 x 450      | 6               | 3.20        | 903557       |
|  |                         | 1200 x 600      | 6               | 4.30        | 903558       |



Fletcher



Commercial interior insulation

## www.insulation.com.au

IICUVI info@insulation.com.au

The colour PINK and Pink® are registered trademarks of Owens Corning and used under licence by Fletcher Insulation.

For further information:

1300 654 444

© Fletcher Insulation Pty Limited 2012. Unless otherwise stated all ™ and are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355. FBS-1 Glasswool Bio-Soluble Insulation® is a registered trademark of ICANZ. FLY28 Revision 0 Issue Date 17012014