













e-form engineered LVL concrete formwork beams e-form beams are purposedesigned for the high load-bearing and corrosive environment of the concrete formwork industry.

The use of slow growing plantation timber veneers makes e-form one of the highest load-bearing formwork LVL beams in Australia.

A high wax loading in the moisture-repellent coating improves the dimensional stability of e-form, extending its life and cost effectiveness.

Features

- Highest strength, yet light to handle.
- High wax content moisture repellent protective coating for improved dimensional stability.
- Engineered straightness and consistent performance.
- Manufactured in lengths up to 12m, minimising wastage.
- Chamfered edges for comfortable handling.
- Manufactured from 100% plantation timbers.



Quality

- Manufactured in a quality controlled manufacturing environment in accordance with AS/NZS 4357
 Structural Laminated Veneer Lumber.
- Product and manufacturing processes meet the stringent occupational health and safety requirements of the commercial and industrial construction industry.

Use of e-form Data

The tables and other technical data provided in this publication are only applicable for e-form (manufactured by Wesbeam), which is one of the highest load-bearing LVL concrete formwork beam available in Australia. This data should not be used for lookalike or substitution products: Use of the e-form data for look-alike or substitution products could result in unsafe or unsatisfactory performance.

Standard Verical Forms : Maximum Height : 2000mm







Plywood formface specification - maximum height 2000mm							
Construction	Stress grade	Length or face grain orientation					
17-10-7	F11	vertical only					
17-10-7	F14	horizontal or vertical					
17-15-7	F14	horizontal or vertical					

Standard Verical Forms : Maximum Height : 3000mm





Maximum Height : 3000mm

Section

Plywood formface specification - maximum height 3000mm								
Construction	Stress grade	Length or face grain orientation						
17-10-7	F11	vertical only						
17-10-7	F22	horizontal or vertical						
17-15-7	F17	horizontal only						



- 2. Design based upon full fluid pressure.
- 3. Formface specifications assume plywood is continuous over at least 3 spans.
- Holes for tie-rods must not be bored through any e-form component.
- 5. For plywood specifications refer AS/NZS 6669

Maximum Height : 3300mm

This form may be used for a reduced height down to 2700mm simply by deleting the top 600mm

Section Maximum Height : 4000mm

This form may be used for a reduced height down to 3400mm simply by deleting the top 600mm

e-form Bearers Supporting Concrete Slabs

Concrete Slab	Nominal Size	Bearer Spacing (mm)											
(mm)	(mm)	900	1200	1500	1800	2100	2400	900	1200	1500	1800	2100	2400
						Maxir	num Be	arer Sp	an (m)				
			Suppor	ting Sin	gle Spai	n Joists		S	upportin	g Contir	nuous S	pan Jois	sts
100	95x65	2.0	1.9	1.7	1.6	1.6	1.5	2.0	1.8	1.7	1.6	1.5	1.5
100	150x77	3.4	3.1	2.9	2.7	2.6	2.5	3.4	3.1	2.8	2.7	2.5	2.4
450	95x65	1.9	1.7	1.6	1.5	1.4	1.3	1.8	1.7	1.5	1.5	1.4	1.3
150	150x77	3.1	2.8	2.6	2.5	2.3	2.2	3.0	2.8	2.6	2.4	2.3	2.2
200	95x65	1.7	1.6	1.5	1.4	1.3	1.2	1.7	1.5	1.4	1.3	1.3	1.2
	150x77	2.9	2.6	2.4	2.3	2.2	2.1	2.8	2.6	2.4	2.2	2.1	2.0
	95x65	1.5	1.4	1.3	1.2	1.2	1.1	1.5	1.4	1.3	1.2	1.1	1.1
300	150x77	2.6	2.3	2.2	2.0	1.9	1.9	2.5	2.3	2.1	2.0	1.9	1.8
100	95x65	1.4	1.3	1.2	1.1	1.1	1.0	1.4	1.3	1.2	1.1	1.0	0.9
400	150x77	2.4	2.1	2.0	1.9	1.8	1.7	2.3	2.1	2.0	1.8	1.8	1.7
600	95x65	1.3	1.1	1.1	1.0	0.9	0.9	1.2	1.1	1.0	0.9	0.8	0.7
	150x77	2.1	1.9	1.8	1.7	1.6	1.5	2.1	1.9	1.7	1.6	1.5	1.3
1000	95x65	1.1	1.0	0.9	0.8	0.7	0.6	1.0	0.9	0.7	0.6	0.5	0.5
1000	150x77	1.8	1.6	1.5	1.4	1.2	1.1	1.7	1.6	1.4	1.2	1.0	0.9

Notes for use of Tables

- 1. Design loads in accordance with AS 3610-2010 including 4 kPa for stacked materials for Stage I and Stage III loading.
- Estimated deflections limit span/270.
 For continuous span applications, design is based upon: a) the most conservative of two or three span use
 - b) all spans equally loaded and
 - c) all spans equal.
- Span values may be interpolated for intermediate concrete slab pour thicknesses.
 Bearers supporting joists, installed in accordance with standard formwork construction practices do not require additional intermediate buckling restraint.
- 6. Maximum spans apply for e-form bearers in new or near new condition with moisture content not exceeding 15%.

e-form Joists Supporting Concrete Slabs

Concrete Slab	Nominal Size	Joist Spacings (mm)											
(mm)	(mm)	225	300	400	450	480	600	225	300	400	450	480	600
		Maximum Joist Span (m)											
				Single	Span				(Continuc	ous Spa	n	
100	95 x 47	2.3	2.1	1.9	1.8	1.8	1.7	2.9	2.5	2.2	2.0	2.0	1.8
	95 x 65	2.6	2.3	2.1	2.0	2.0	1.9	3.2	2.9	2.5	2.4	2.3	2.1
	150 x 77	4.2	3.9	3.5	3.4	3.3	3.1	5.2	4.8	4.4	4.1	4.0	3.6
150	95 x 47	2.1	1.9	1.7	1.7	1.6	1.5	2.6	2.3	2.0	1.9	1.8	1.6
	95 x 65	2.3	2.1	1.9	1.9	1.8	1.7	2.9	2.6	2.4	2.2	2.2	1.9
	150 x 77	3.9	3.5	3.2	3.1	3.0	2.8	4.8	4.4	4.0	3.8	3.7	3.3
200	95 x 47	1.9	1.8	1.6	1.5	1.5	1.4	2.4	2.2	1.9	1.8	1.7	1.5
	95 x 65	2.2	2.0	1.8	1.7	1.7	1.6	2.7	2.4	2.2	2.1	2.0	1.8
	150 x 77	3.6	3.3	3.0	2.9	2.8	2.6	4.4	4.0	3.7	3.5	3.5	3.1
300	95 x 47	1.7	1.6	1.4	1.4	1.4	1.3	2.1	1.9	1.7	1.6	1.5	1.4
	95 x 65	1.9	1.8	1.6	1.5	1.5	1.4	2.4	2.2	2.0	1.9	1.8	1.6
	150 x 77	3.2	2.9	2.7	2.6	2.5	2.3	4.0	3.6	3.3	3.2	3.1	2.8
400	95 x 47	1.6	1.5	1.3	1.3	1.2	1.2	2.0	1.8	1.5	1.5	1.4	1.3
	95 x 65	1.8	1.6	1.5	1.4	1.4	1.3	2.2	2.0	1.8	1.7	1.7	1.5
	150 x 77	3.0	2.7	2.5	2.4	2.3	2.1	3.7	3.3	3.0	2.9	2.8	2.5
600	95 x 47	1.4	1.3	1.2	1.1	1.1	1.0	1.7	1.5	1.3	1.3	1.2	1.0
	95 x 65	1.6	1.4	1.3	1.3	1.2	1.1	1.9	1.8	1.6	1.5	1.4	1.3
	150 x 77	2.6	2.4	2.2	2.1	2.0	1.9	3.2	2.9	2.7	2.5	2.5	2.2
1000	95 x 47	1.2	1.1	1.0	1.0	0.9	0.8	1.5	1.3	1.0	0.9	0.8	0.7
	95 x 65	1.3	1.2	1.1	1.1	1.0	1.0	1.7	1.5	1.3	1.2	1.2	0.9
	150 x 77	2.2	2.0	1.8	1.8	1.7	1.6	2.8	2.5	2.2	2.1	2.0	1.7

Notes for use of Tables

1. Design loads in accordance with AS 3610-2010 including 4 kPa for stacked materials for Stage I and Stage III loading.

- Estimated deflections limit span/270.
 For continuous span applications, design is based upon:

a) the most conservative of two or three span use

- b) all spans equally loaded and
- c) all spans equal.
- Span values may be interpolated for intermediate concrete slab pour thicknesses.
 Joists supporting formface sheeting, installed in accordance with standard formwork construction practices do not require additional intermediate buckling restraint.
- 6. Maximum spans apply for e-form in new or near new condition with moisture content not exceeding 15%.

Design Load and Deflection Table for e-form

e-form Section	Span m	Maximum Design	Deflection for Unit	Loac Deflectio	ls for on Limits	Maximum Design	Deflection for Unit	Loads for Deflection Limits	
Size mm x mm		kN/m	Load mm/kN/m	d = L/270 kN/m	d = 3mm kN/m	kN/m	Load mm/kN/m	d = L/270 kN/m	d = 3mm kN/m
			Single	Span			Multiple	e Spans	
95 x 47	0.9	25.2	0.24	14.2	12.7	20.1	0.10	26.7	24.0
	1.2	15.0	0.74	6.0	4.0	15.0	0.31	11.3	7.6
	1.5	9.6	1.82	3.1	1.7	9.6	0.75	5.8	3.1
	1.8	6.6	3.77	1.8	0.8	6.6	1.56	3.3	1.5
	2.1	4.9	6.98	1.1	0.4	4.9	2.90	2.1	0.8
	2.4	3.7	11.91	0.7	0.3	3.7	4.94	1.4	0.5
95 x 65	0.9	34.8	0.17	19.6	17.6	27.9	0.07	36.9	33.2
	1.2	20.7	0.54	8.3	5.6	20.7	0.22	15.6	10.5
	1.5	13.2	1.31	4.2	2.3	13.2	0.55	8.0	4.3
	1.8	9.2	2.73	2.4	1.1	9.2	1.13	4.6	2.1
	2.1	6.8	5.05	1.5	0.6	6.8	2.10	2.9	1.1
	2.4	5.2	8.61	1.0	0.3	5.2	3.58	1.9	0.7
150 x 77	0.9	65.1	0.04	91.3	82.1	52.1	0.02	172.2	155.0
	1.2	48.9	0.12	38.5	26.0	39.1	0.05	72.7	49.0
	1.5	39.1	0.28	19.7	10.6	31.3	0.12	37.2	20.1
	1.8	27.1	0.58	11.4	5.1	26.1	0.24	21.5	9.7
	2.1	19.9	1.08	7.2	2.8	19.9	0.45	13.6	5.2
	2.4	15.3	1.85	4.8	1.6	15.3	0.77	9.1	3.1

Notes for use of Tables

1. Shaded values of 'loads for deflection' exceed the maximum design load for the strength limit state.

- 2. Estimated deflections limit span/270. A deflection limit of 3mm is also included in the Table as some formwork designers may wish to use a tighter deflection limit.
- 3. To satisfy the strength limit state the design load calculated using factored load combinations given in AS 3610 must be less than the Maximum Design Load given in the Table.
- Maximum design load, based on capacity, is calculated using Ø = 0.90, k1 = 0.94, k4 = 1.0, k6 = 0.9 & k12 = 1.0 - refer AS 1720.1.
- 5. Values given in the Table apply for e-form in new or near new condition with moisture content not exceeding 15%.
- 6. Values of load or deflection may not be interpolated for spans intermediate to those included in the table.
- 7. For multiple spans, values given have been determined on the basis of all spans being equal, uniform and equal loads to all spans and the most conservative of two or three span use.

Structural Design

The Tabular data and standard designs listed in this publication have been prepared in accordance with the following Australian Standards; AS1720.1 - 2010 - Timber structures Part 1: Design methods AS3610 - 2010 - Formwork for concrete AS/NZS 6669 - Plywood - Formwork

Design Assumptions

The following design assumptions are used in the preparation of the Tables in this publication, unless otherwise noted.

Capacity factor	Ø = 0.90
Duration of Load Factor - AS1720.1 Part 2.4	
 Strength –duration of peak action = 5 days 	<i>k</i> 1 = 0.94
– Moisture content –mc \leq 15%	<i>k</i> 4 = 1.00
− Moisture content – mc \ge 15% and \le 20%	<i>k</i> 4 = 0.85
 Temperature – in coastal regions of Queensland north of latitude 25°S, and all other regions of Australia north of latitude 16°S 	<i>k</i> 6 = 0.90
 Temperature – all other regions of Australia 	<i>k</i> 6 = 1.00
Strength sharing - bearers, joists, soldiers and whalers	<i>k</i> 9 = 1.00
Stability factor	<i>k12</i> = 1.00
Deformation factor – AS1720.1 Fig 2.1 (Duration of load – 5 days)	
$- mc \le 15\%$	J2 = 1.00
$-$ mc \geq 15% and \leq 20%	J2 = 1.00
$-$ mc $\ge 25\%$ $-$ Moisture content $-$ mc $\le 15\%$	J2 = 1.50
Joint Group Classification – AS1720.1 Part 4.1.2 Joint groups	
 Design Joint Group – Seasoned LVL – Nails, bolts and screws 	JD4
Cutting, Notching and Dimensional Changes	
Design Loads and Design Capacities listed in the Tables apply to Wesbeam e-form LVL which has NOT been cut, notched or the member dimensions changed/altered.	

Characteristic Properties - e-form LVL

The Characteristic Design Properties, member Rigidity (El_{xx}), member Bending Capacity (M_d) and member Shear Capacity (V_d) are available for component formwork design Engineers. Please contact Wesbeam Technical Services for e-form LVL Design information.

e-form LVL Weight

Nominal Size D x B (mm)	Mass of Member (kg/m)
95 x 47	2.7
95 x 65	3.8
150 x 77	7.1

Veneer			Joint Grou	qu		
	Thickness Species	Constant through the product thickness Plantation timber	Finish	JD4 – for nails, bolts and screws		
Moistura		Inner plies – scarf and/or butt jointed		Unsanded faces, sawn edges and arrised edges. Each piece of Wesbeam e-form LVL is coated with		
8%–15% (at time of despatch)			a high wax content coloured moisture repellent protective application.			
Dimensio	nal Toleranc	es	Branding			
	Available of	n request		Each piece of Wesbeam e-form LVL is branded as		
Straightness			least once with the product name for identification			
	Available on request			control standards		
Density			Storage			
650 kg/m ³ (approximately)		(approximately)	0	Store on level bearers at maximum 1800mm centres		
Adhesive				well clear of the ground, and cover to keep dry but		
Pond	Phenolic –	AS 2754.1	Source			
Бона	T	0/1170 0000 0		Plantation timber certified to AS4707-2006 / PEFC		
	Iype A – A	S/NZS 2098.2	Condition			
				Untreated		



PO Box 217 Wanneroo, WA 6946 F (08) 9306 0444 190 Pederick Road Australia

T (08) 9306 0400

- E wesbeam@wesbeam.com
- Neerabup, WA 6031 W www.wesbeam.com

© Wesbeam Pty Limited ABN 89 004 268 017 Date of publication: April 2015